

Actual4Labs

Pass Your Next Certification Exam Fast!

Everything you need to prepare, learn & pass your certification exam easily.

Login / Register

Shopping Cart (0)

Search...



Online Test Engine

Instant Online Access, Test History and Performance Review, Supports Windows / Mac / Android / iOS, etc. →

Desktop Test Engine

Installable Software Application, Simulates Real Exam Environment, Supports MS Operating System, Practice Offline Anytime. →

PDF Format

Printable PDF Format, Prepared by IT Experts, Study Anywhere, Anytime, Free PDF Demo Available. →

Choose the version that fits your needs

| | PDF Version | Desktop Test Engine | Online Test Engine |
|---|-------------|---------------------|--------------------|
| Latest and Up-to-Date exam dumps with real exam questions answers. | ✓ | ✓ | ✓ |
| Get 12-Months free updates without any extra charges. | ✓ | ✓ | ✓ |
| Experience same exam environment before appearing in the certification exam. | ✗ | ✓ | ✓ |
| 100% exam passing guarantee in the first attempt. | ✓ | ✓ | ✓ |
| 20% discount on more than one license and 30% discount on 5+ license purchases. | ✗ | ✓ | ✓ |
| 100% secure purchase on SSL. | ✓ | ✓ | ✓ |
| Completely private purchase without sharing your personal info with anyone. | ✓ | ✓ | ✓ |

<http://www.actual4labs.com>

Excellent Quality Exam Dumps Questions Never Let You down -
Actual4Labs

Exam : **H11-851_V3.0**

Title : **HCIA-Video Conference V3.0**

Vendor : **Huawei**

Version : **DEMO**

NO.1 Regarding the C1oudlink terminal, is the following description correct? ()

- A. The Box 300 does not require a VPT300 to support intelligent navigation.
- B. Bar 300 supports a maximum resolution of 4K.
- C. The Bar 300, Box 300, and Box 600 all support wireless data sharing.
- D. The Box 600 has a built-in camera and stereo.

Answer: C

NO.2 The range of sound frequencies that the human ear can recognize is ().

- A. 90~40KHZ
- B. 20~20KHZ
- C. 10~10KHZ
- D. 30~30KHZ

Answer: B

NO.3 Switch Center is located in the video product stack at ().

- A. Service support layer
- B. User Access Layer
- C. Business Management
- D. Media Processing Layer

Answer: C

NO.4 System administrators and meeting administrators log in to SMC3.0 by entering the IP address/sys-portal of https://SMC3.0 in the address bar of the browser and logging in.

- A. False
- B. True

Answer: B

NO.5 Video conferencing systems are generally composed of terminals, communication networks, MCUs, GKs and other parts.

- A. True
- B. False

Answer: A

NO.6 The video conferencing system is generally composed of several parts, such as terminals, MCUs, gateways, and management platforms. ()

- A. True
- B. False

Answer: A

NO.7 Regarding the H323 protocol, is the following description correct?

- A. Video encoding protocol, audio encoding protocol, and media transmission protocol belong to the media control class.
- B. Media control class protocol is responsible for conference control and terminal calls.

- C. The secondary stream data transmission protocol is not present.
- D. The terminal control management class protocol is responsible for the transmission of audio and video code streams.
- E. 323 in the protocol stack.

Answer: D

NO.8 After IdeaHub is successfully activated, you can join the scheduled meeting with the click of ().

- A. Call Recent Call Log
- B. Caller Call Set
- C. Meeting Schedule
- D. Call Terminal IP

Answer: C

NO.9 TE30 does not support HDMI interface output ().

- A. True
- B. False

Answer: B

NO.10 Regarding wireless access, the following description is correct? ().

- A. ClouLink terminal, when WiFi clients are enabled, support automatic scanning and connection of wireless access points, and support dynamic ip address acquisition , which cannot be modified manually.
- B. CloudLink endpoints support enabling both clients and hot-spots, and only support 2.4GHz wireless communication.
- C. When the ClouL.ik terminal enables the WiFi hot-spot, the PC can connect directly to the hot-spot without cables and connect to the wireless network
- D. After the CoudLik terminal enables the WiFi client, it supports automatic scanning and connection of wireless access points, supports static setting of IP addresses, and cannot be dynamically obtained.

Answer: C

NO.11 The video output of TE40, the output GUI interface is ().

- A. S-video
- B. Video output 2
- C. Video output 1
- D. Video output 3

Answer: B,C,D

NO.12 Regarding hardware conference room terminals and software conference room terminals, what is the following description incorrect? ()

- A. Hardware Conference Room Terminal supports unmanageable mode and manageable mode added to SMC3.0.
- B. Software Conference Room Terminal only supports unmanageable way of adding to SMC 3.0.
- C. Both hardware conference room terminals and software conference room terminals support batch

addition to SMC3.0.

D. Hardware conference room terminals only support added to SMC3.0 in a manageable way.

Answer: D

NO.13 The INVITE transaction consists of a three-way handshake, in which the client sends INVITE, the server sends a response, and the client sends an ACK ()

A. True

B. False

Answer: A

NO.14 The following is () that belongs to the video conferencing data transmission standard protocol. /

A. T120

B. G711

C. H264

D. MPEG-4

Answer: A

NO.15 On the same TV, the human eye watches 720P video, and it must not be as clear as 1080P video. ()

A. True

B. False

Answer: A

NO.16 Use a Type-C cable to connect your Touch and a power adapter to charge your Touch.

A. False

B. True

Answer: B

NO.17 Whether the MCU and SMC are successfully connected can be determined by the GK status of the MCU registration. ()

A. False

B. True

Answer: A

NO.18 IdeaHub does not support audio output via an external HDMI display. ()

A. True

B. False

Answer: B

NO.19 Regarding "multipoint meetings", the following description is correct?()

A. A multi-point meeting is a meeting convened in three or more venues.

B. The terminal convenes a multipoint meeting and needs to use the MCU as the meeting convening resource.

C. After a peer-to-peer call is established, you can set up a multipoint conference by calling other terminals point by point.

D. Multipoint conferencing supports hybrid H323 and SIP conferencing.

Answer: A,B,C,D

NO.20 The 320.H.323 standard belongs to the () network

A. Circuit-switched

B. Packet-switched

C. Link Switching

D. Light Exchange

Answer: B

NO.21 The main role of the 281.H.245 protocol is ().

A. Real-time transmission

B. Media Encoding

C. Video encoding

D. Competency Consultation

Answer: B,D

NO.22 Enterprise construction of conference television system, MCU and business system in the private network, public network terminal access, at this time if the realization of two different network segments of the terminal equipment between the multi-media communication, you can set the MCU GE1 working mode as ().

A. Back up

B. Load sharing

C. Ride the wall

D. Dynamically switch

Answer: C

NO.23 Which of the following interfaces supports audio signals ().

A. RCA

B. HDMI

C. S-VIDEO

D. DVI

Answer: A,B

NO.24 In a video conference, the camera () feature is used to close-up a participant.

A. Pangraphic localization

B. Large wide angle

C. Lens zoom

D. WDR

Answer: A,C,D

NO.25 The H245 protocol is transmitted on a UDP layer basis ().

- A. False
- B. True

Answer: A

NO.26 After the meeting is recorded, the system automatically transcodes the live streaming resources when there is room for them, so that the resources of the RSE6500 are fully utilized, a process known as this ()?

- A. Live
- B. On demand
- C. Recording
- D. Offline transcoding

Answer: D

NO.27 SMC2.0 deployment requires a () database.

- A. Microsoft SQL Server
- B. GaussDB
- C. Oracle
- D. MySQL

Answer: A

NO.28 Regarding CloudMCU multi-stream conferencing, the following description is incorrect?().

- A. Multi-stream meetings do not support multi-screen broadcasting.
- B. Pure SVC conferencing consumes more resources than AVC conferencing.
- C. Multi-stream hybrid conferencing supports AVC and SVC terminal access, supports cascading with fully adaptable conferences, and also supports cascading with multi-stream hybrid conferencing.
- D. Compared to AVC conferencing, the codec is done by the terminal side in the SVC conferencing, and the NCU is only responsible for forwarding.

Answer: A

NO.29 Video input2 can be used as a TE40 secondary input interface ().

- A. True
- B. False

Answer: A

NO.30 Normal user rights for CloudRSE include ().

- A. Recording management
- B. Video Viewing and Downloading
- C. User management
- D. Video Management

Answer: B